



Available as  
**PEFC or FSC**  
certified paper on  
request

### Technical data

Basis weight [g/m <sup>2</sup> ] ISO 536	45 ♦	48	51	54	57
Brightness D65/10° [%] ISO 2470	77	77	77	77	77
Colour D65/10° [%] L*	91	91	91	91	91
a*	-0.7	-0.7	-0.7	-0.7	-0.7
b*	2.7	2.7	2.7	2.7	2.7
Opacity [%] ISO 2471	88	89	90	91	92
Gloss Hunter 75° [%] ISO 8245/1	44	44	46	46	47
Gloss Lehmann 75° [%] ① ISO 8254/1	41	41	43	44	44
Roughness PPS 10 [µm] ISO 8791-4	1.1	1.1	1.1	1.1	1.1
Bulk [cm <sup>3</sup> /g] ③	0.9	0.9	0.9	0.9	0.9

♦ On request

Subject to change. 07/2009

① The process control is based on Hunter gloss – the Lehmann gloss specification serves as a reference value only

③ No guaranteed value – subject to production variations

Please check for availability as all basis weights may be subject to production requirements.

#### Product description:

MY PLUS is an improved high-bright SC-A grade for all high quality print production.

#### Composition:

20 % chemical pulp  
80 % mechanical pulp

#### Examples of use:

Catalogues, magazines and high quality advertising materials

#### Reel specification:

– Minimum width: 41 cm  
– Maximum width: 360 cm  
– Diameter: max. 130 cm  
– Core diameter: 76 mm or 150 mm



Available as  
**PEFC**  
certified paper on  
request

<b>Technical data</b>					
Basis weight [g/m <sup>2</sup> ] ISO 536	45	48	51	54	57
Brightness D65/10° [%] ISO 2470	75	75	75	75	75
Colour D65/10° [%] L*	91	91	91	91	91
a*	-0.7	-0.7	-0.7	-0.7	-0.7
b*	2.7	2.7	2.7	2.7	2.7
Opacity [%] ISO 2471	88	89	90	91	92
Gloss Hunter 75° [%] ISO 8245/1	44	44	46	46	47
Gloss Lehmann 75° [%] <sup>Ⓢ</sup> ISO 8254/1	41	41	43	44	44
Roughness PPS 10 [µm] ISO 8791-4	1.2	1.2	1.2	1.2	1.2
Bulk [cm <sup>3</sup> /g] <sup>Ⓢ</sup>	0.9	0.9	0.9	0.9	0.9

<sup>Ⓢ</sup> The process control is based on Hunter gloss – the Lehmann gloss specification serves as a reference value only

Subject to change. 04/2009

<sup>Ⓢ</sup> No guaranteed value – subject to production variations

Please check for availability as all basis weights may be subject to production requirements.

**Product description:**

MY PLUS is an improved high-bright SC-A grade for all high quality print production.

**Composition:**

20 % chemical pulp  
80 % mechanical pulp

**Examples of use:**

Catalogues, magazines and high quality advertising materials

**Reel specification:**

- Minimum width: 60 cm
- Maximum width: 520 cm
- Diameter: max. 150 cm
- Core diameter: 76 mm or 150 mm