



Available as
PEFC or FSC
certified paper on
request

Technical data

Basis weight [g/m ²] ISO 536	45	48.8	52	55	60
Brightness C/2° [%] ISO 2470	68	68	68	68	68
Colour C/2° [%] L*	87.0	87.0	87.0	87.0	87.0
a*	0.1	0.1	0.1	0.1	0.1
b*	1.3	1.3	1.3	1.3	1.3
Opacity [%] ISO 2471	94	94	95	95	96
Roughness PPS 10 [µm] [Ⓢ] ISO 8791-4	2.2	2.2	2.2	2.2	2.2
Roughness Bendtsen [ml/min] ISO 8791/2	30	30	30	30	30
Bulk [cm ³ /g] [Ⓢ]	1.1	1.1	1.1	1.1	1.1
Gloss 75°	24	24	24	25	25

[Ⓢ] No guaranteed value – subject to production variations

Subject to change. 09/2009

[Ⓢ] PPS serves as a reference value only – the production process is based on measurement by Bendtsen

Please check for availability as all basis weights may be subject to production requirements.

Product description:

MY 70 HS is a calendered improved newsprint quality especially made for HSWO requirements.

Composition:

Min. 90 % DIP

Examples of use:

Magazines, catalogues, special editions, advertising supplements

Reel specification:

- Minimum width: 40 cm
- Maximum width: 300 cm
- Diameter: max. 125 cm
- Core diameter: 76 mm or 150 mm

Reel specification:

Paper type 5 according to ISO 12647-2