



Available as  
**PEFC or FSC**  
 certified paper on  
 request

<b>Technical data</b>					
Basis weight [g/m <sup>2</sup> ] ISO 536	45	48.8	52	55	60
Brightness C/2° [%] ISO 2470	68	68	68	68	68
Colour C/2° [%] L*	87.0	87.0	87.0	87.0	87.0
a*	0.1	0.1	0.1	0.1	0.1
b*	1.3	1.3	1.3	1.3	1.3
Opacity [%] ISO 2471	94	94	95	95	96
Roughness PPS 10 [µm] <sup>Ⓢ</sup> ISO 8791-4	3.8	3.8	3.8	3.8	3.8
Roughness Bendtsen [ml/min] ISO 8791/2	125	125	125	125	125
Bulk [cm <sup>3</sup> /g] <sup>Ⓢ</sup>	1.4	1.4	1.4	1.3	1.3

<sup>Ⓢ</sup> No guaranteed value – subject to production variations

Subject to change. 09/2009

<sup>Ⓢ</sup> PPS serves as a reference value only – the production process is based on measurement by Bendtsen  
 Please check for availability as all basis weights may be subject to production requirements.

**Product description:**

MY 70 is a machine finished improved newsprint quality which is especially produced for the Coldset market and suited to all CSWO requirements.

**Reel specification:**

- Minimum width: 40 cm
- Maximum width: 300 cm
- Diameter: max. 125 cm
- Core diameter: 76 mm or 150 mm

**Composition:**

Min. 90 % DIP

**Reel specification:**

Paper type 5 according to ISO 12647-2

**Examples of use:**

Magazines, catalogues, premium newspaper, special editions, supplements and brochures.