



Available as
FSC
certified paper on
request

Technical data							
Basis weight [lbs/3,300 sq ft]	25	26	28	30	32	33	35
Gloss (%)	41	41	43	43	43	47	47
Brightness (ISO)	66	66	67	67	68	68	68
Opacity (%)	83	83	86	88	89	89	90
Smoothness	1.2	1.2	1.2	1.2	1.1	1.1	1.1
Bulk/Caliper	1.6	1.6	1.65	1.75	1.8	1.8	1.9

The above specifications are target values. Please consult with your MYLLYKOSKI SALES representative for question about product specifications and availability.
All basis weights may be subject to production requirements.

Subject to change. 11/2009

Product description:

World-class SCA paper from the mill that pioneered the production of supercalendered paper in the USA. Special PCC filler for opacity and brightness, excellent side-to-side consistency, ultra-lightweight availability.

Composition:

Kraft in the sheet is 18.5 %
Mechanical pulp in the sheet is 51.5 %
Filler in the sheet is 25 %

Examples of use:

High-quality catalogues, magazines and retail inserts

Reel specification:

- Minimum width: 14.75 in./37.465 cm
- Maximum width: 132 in./335.28 cm
- Core diameter: 3 in. or 6 in.
- Reel diameter: 50 in. Maximum
- Machine trim 281 in/713.74 cm