

Technical data

Basis weight [g/m ²] ISO 536	57	65
Brightness D65/10° [%] ISO 2470	84	84
Colour D65/10° [%] L*	93	93
a*	0.6	0.6
b*	-3.5	-3.5
Opacity [%] ISO 2471	91	93
Gloss Hunter 75° [%] ^② ISO 8245/1	31	31
Gloss Lehmann 75° [%] ISO 8254/1	30	30
Roughness PPS 10 [µm] ^③ ISO 8791-4	1.1	1.1
Bulk [cm ³ /g]	1.0	1.0

② The process control is based on Lehmann gloss – the Hunter gloss specification serves as a reference value only

Subject to change. 02/2010

③ No guaranteed value – subject to production variations

Please check for availability as all basis weights may be subject to production requirements.

Product description:

MY VOLUME *gravure* is a lightweight wood-containing coated rotogravure paper with a silk finish and a 20 % higher volume.

Composition of the certified raw material:

Coating weight: 33 % approx.

Base paper composition

(depending on basis weight):

45–55 % mechanical pulp

30–35 % chemical pulp

10–20 % DIP

Examples of use:

Sustainable high quality brochures, lifestyle magazines, exclusive catalogues and inserts

Reel specification:

– Minimum width: 50 cm

– Maximum width: 450 cm

– Diameter: max. 135 cm

– Core diameter: 76 mm or 150 mm