



Available as  
**PEFC or FSC**  
certified paper on  
request

| <b>Technical data</b>                            |                 |      |      |      |      |
|--|-----------------|------|------|------|------|
| Basis weight [g/m <sup>2</sup> ]<br>ISO 536      | 45 <sup>♦</sup> | 48   | 51   | 55   | 58   |
| Brightness D65/10° [%]<br>ISO 2470               | 67              | 67   | 68   | 68   | 68   |
| Colour D65/10° [%]<br>L*                         | 88.2            | 88.2 | 88.5 | 88.5 | 88.5 |
| a*   | -1.1            | -1.1 | -1.1 | -1.1 | -1.1 |
| b*   | 3.5             | 3.5  | 3.5  | 3.3  | 3.3  |
| Opacity [%]<br>ISO 2471                          | 90              | 91   | 92   | 92   | 93   |
| Gloss Hunter 75° [%]<br>ISO 8245/1               | 32              | 36   | 36   | 36   | 36   |
| Gloss Lehmann 75° [%] <sup>Ⓢ</sup><br>ISO 8254/1 | 29              | 33   | 33   | 33   | 33   |
| Roughness PPS 10 [µm] <sup>Ⓢ</sup><br>ISO 8791-4 | 1.9             | 1.8  | 1.7  | 1.6  | 1.6  |
| Bulk [cm <sup>3</sup> /g] <sup>Ⓢ</sup>           | 1.1             | 1.1  | 1.1  | 1.0  | 1.0  |

♦ On request

Subject to change. 02/2008

Ⓢ The process control is based on Hunter gloss – the Lehmann gloss specification serves as a reference value only

Ⓢ No guaranteed value – subject to production variations

Please check for availability as all basis weights may be subject to production requirements.

**Product description:**

MY JOY is the reliable SC-Offset magazine paper with a clean surface, innovative substance range and great runnability.

**Composition:**

Min. 85 % DIP

**Examples of use:**

Magazines, catalogues, advertising supplements

**Reel specification:**

- Minimum width: 40 cm
- Maximum width: 380 cm
- Diameter: max. 135 cm
- Core diameter: 76 mm or 150 mm