



Available as  
**PEFC**  
 certified paper on  
 request

### Technical data

	60	70	80	90	100
Basis weight [g/m <sup>2</sup> ] ISO 536	60	70	80	90	100
Brightness D65/10° [%] ISO 2470	90	90	91	91	91
Colour D65/10° [%] L*	93	93	93	93	93
a*	0.6	0.6	0.6	0.6	0.6
b*	-4.5	-4.5	-4.5	-4.5	-4.5
Opacity [%] ISO 2471	89	94	95	96	97
Gloss Hunter 75° [%] <sup>Ⓜ</sup> ISO 8245/1	18	18	18	18	18
Gloss Lehmann 75° [%] ISO 8254/1	15	15	15	15	15
Roughness PPS 10 [µm] <sup>Ⓢ</sup> ISO 8791-4	4.0	4.0	4.0	4.0	4.0
Bulk [cm <sup>3</sup> /g]	1.2	1.2	1.2	1.2	1.2

<sup>Ⓜ</sup> The process control is based on Lehmann gloss – the Hunter gloss specification serves as a reference value only

Subject to change. 03/2010

<sup>Ⓢ</sup> No guaranteed value – subject to production variations

#### Product description:

MY VOLUME is a high bright, matt-coated high volume paper for heatset web offset with excellent runnability.

#### Composition:

Base paper composition  
 (depending on basis weight):  
 35–45 % chemical pulp  
 65–55 % mechanical pulp

#### Examples of use:

Supplements, brochures, magazines and direct mails in high quality

#### Reel specification:

- Minimum width: 30 cm (packed in pairs)
- Maximum width: 250 cm
- Diameter: max. 125 cm
- Core diameter: 76 mm or 150 mm

#### Prepress information:

Prepress profile for paper type 2  
 according ISO 12647-2 recommended