



Available as
PEFC
certified paper on
request

Technical data

	60 [♦]	70	75	80	90	100	115	135
Basis weight [g/m ²] ISO 536	60 [♦]	70	75	80	90	100	115	135
Brightness D65/10° [%] ISO 2470	92	93	93	94	94	94	94	94
Colour D65/10° [%] L*	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5
a*	0.5	0.6	0.6	0.7	0.7	0.7	0.7	0.7
b*	-5.7	-5.8	-5.8	-6.0	-6.0	-6.0	-6.0	-6.0
Opacity [%] ISO 2471	89	92	93	94	95	97	97	98
Gloss Hunter 75° [%] [Ⓜ] ISO 8245/1	19	19	19	19	20	21	21	21
Gloss Lehmann 75° [%] ISO 8254/1	16	16	16	16	17	18	18	18
Roughness PPS 10 [µm] [Ⓢ] ISO 8791-4	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
Bulk [cm ³ /g] [Ⓢ]	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1

♦ On request

Subject to change. 02/2008

Ⓜ The process control is based on Lehmann gloss – the Hunter gloss specification serves as a reference value only

Ⓢ No guaranteed value – subject to production variations

Product description:

MY BRITE *matt* is a high bright wood containing light weight coated (LWC) and medium weight coated (MWC) matt paper for HSWO with a blue-white shade and excellent readability.

Composition:

Coating weight: 33 % approx.
Base paper composition
(depending on basis weight):
35–45 % chemical pulp
65–55 % mechanical pulp

Examples of use:

High quality supplements, brochures, magazines, catalogues

Reel specification:

- Minimum width: 30 cm (packed in pairs)
- Maximum width: 250 cm
- Diameter: max. 125 cm
- Core diameter: 76 mm or 150 mm

Prepress information:

Prepress profile for paper type 2
according ISO 12647-2 recommended



Available as
PEFC or FSC
certified paper on
request

Technical data

	60	65	70	75	80	90
Basis weight [g/m ²] ISO 536	60	65	70	75	80	90
Brightness D65/10° [%] ISO 2470	93	93	93	93	93	93
Colour D65/10° [%] L*	93.5	93.5	93.5	93.5	93.5	93.5
a*	0.6	0.6	0.6	0.6	0.6	0.6
b*	-5.5	-5.5	-5.5	-5.5	-5.5	-5.5
Opacity [%] ISO 2471	93	94	95	95	96	97
Gloss Hunter 75° [%] ISO 8245/1	20	20	20	20	20	20
Gloss Lehmann 75° [%] ^① ISO 8254/1	18	18	18	18	18	18
Roughness PPS 10 [µm] ^② ISO 8791-4	2.5	2.5	2.5	2.5	2.5	2.5
Bulk [cm ³ /g] ^③	1.1	1.1	1.1	1.1	1.1	1.1

① The process control is based on Hunter gloss – the Lehmann gloss specification serves as a reference value only.

Subject to change. 04/2009

② No guaranteed value – subject to production variations.

Product description:

MY BRITE *matt* is a high bright wood containing light weight coated (LWC) and medium weight coated (MWC) matt paper for HSWO with a modern blue-white shade.

Composition:

Coating weight: 33 % approx.
Base paper composition
(depending on basis weight):
35–45 % chemical pulp
65–55 % mechanical pulp

Examples of use:

High quality supplements, brochures, magazines, catalogues

Reel specification:

- Minimum width: 40 cm (packed in pairs)
- Maximum width: 268 cm
- Diameter: max. 130 cm
- Core diameter: 76 mm or 150 mm

Prepress information:

Prepress profile for paper type 2
according ISO 12647-2 recommended