



Available as  
**PEFC or FSC**  
certified paper on  
request

Technical data				
Basis weight [g/m <sup>2</sup> ] ISO 536	45	48	51	55
Brightness C/2° [%] ISO 2470	66	66	66	66
Colour D65/10° [%] L*	88.2	88.2	88.2	88.2
a*	-0.9	-0.9	-0.9	-0.9
b*	4.4	4.4	4.4	4.4
Opacity [%] ISO 2471	92	93	93	94
Gloss Hunter 75° [%] ISO 8245/1	36	36	36	36
Gloss Lehmann 75° [%] <sup>①</sup> ISO 8254/1	33	33	33	33
Roughness PPS 10 [µm] ISO 8791-4	1.7	1.5	1.4	1.4
Bulk [cm <sup>3</sup> /g] <sup>②</sup>	0.96	0.96	0.92	0.91

① The process control is based on Hunter gloss – the Lehmann gloss specification serves as a reference value only

Subject to change. 01/2009

② No guaranteed value – subject to production variations

Please check for availability as all basis weights may be subject to production requirements.

**Product description:**

MY JOY *gravure* is a leading SC-B rotogravure quality with high recycled fibre content.

**Composition:**

ca. 75 % DIP

**Examples of use:**

Magazines, catalogues and supplements

**Reel specification:**

- Minimum width: 60 cm
- Maximum width: 432 cm
- Diameter: max. 150 cm
- Core diameter: max. 150 mm